
# GUARDIAN Metallic Bearing Isolator

# The Metallic Isolator that can be installed on site...

- Noncontacting seal
- No wear on shaft or bronze components
- No internal metal to metal contact
- One piece unitized design
- Easy installation No arbor press required
- Meets NEMA MG 1-2003
- Surpasses IEEE 841-2001 Test Standards
- Available in flangeless design

### **Design Parameters**

- Temperature: -30°F (-34°C) to 400°F (204°C)
- Maximum shaft-to-bore misalignment to ±0.020" (0.51mm)
- Axial motion is ±0.025" (0.64mm)
- Maximum surface speed 12,000 fpm (61 m/s)
- No internal o-rings



Patents Pending



Service.

Inventory.

Solutions.



## KLOZURE® OIL SEALS & BEARING ISOLATORS **GUARDIAN™ Metallic Bearing Isolator**

### **Bearing Isolator Testing**

	IEEE Dust	IEEE Water	Durability	Hand Installable
GUARDIAN™	Pass	Pass	Pass	Yes
Competitor "A"	Fail	Fail	T.B.D.	Yes
Competitor "B"	Pass	Pass	T.B.D.	No
ISO-GARD®	Pass	Pass	Pass	Yes
			Patented Cam- Installs Without and Retains Se No Bronze to Bronze Contact	Arbor Press al in Housing



AUTHORIZED DISTRIBUTOR

#### WARNING:

Properties/applications shown throughout this brochure are typical. Your specific application should not be undertaken without independent study and evaluation for suitability. For specific application recommendations consult Garlock. Failure to select the proper sealing products could result in property damage and/or serious personal injury. Performance data published in this brochure has been developed from field testing, customer field reports and/or in-house testing.

While the utmost care has been used in compiling this brochure, we assume no responsibility for errors. Specifications subject to change without notice. This edition cancels all previous issues. Subject to change without notice.

GARLOCK is a registered trademark for packings, seals, gaskets, and other products

© Garlock 2004 All rights reserved worldwide.



ISO 9001:2000 Cert. #001762

# Emerson Bearing A Division of Bearing Enterprises, Inc.

Service. Solutions. Inventory.

#### **Klozure Oil Seals & Bearing Isolators**

A Division of Garlock Sealing Technologies 1666 Division Street Palmyra, New York 14522 USA

1.315.597.4811

Fax: 1.315.597.3216

Toll Free: 1.866.KLOZURE (1.866.556.9873) Toll Free Fax: 1.866.OILSEAL (1.866.645.7325)

Visit Klozure:

www.klozure.com

#### Other Garlock brand facilities are located in:

Columbia, SC, USA	1-803-783-1880	Fax: 1-803-783-4279
Houston, TX, USA	1-281-459-7200	Fax: 1-281-458-0502
Sydney, Australia	61-2-9793-2511	Fax: 61-2-9793-2544
São Paulo, Brazil	55-11-4352-6161	Fax: 55-11-4352-8181
Brantford, Canada	1-519-753-8671	Fax: 1-519-758-2265
Sherbrooke, Canada	1-819-563-8080	Fax: 1-819-563-5620
Dubai, UAE	971-4-8833652	Fax: 971-4-8833682
West Yorkshire, England	44-1422-313600	Fax: 44-1422-313601
Saint-Étienne, France	33-4-7743-5100	Fax: 33-4-7743-5151
Neuss, Germany	49-2131-3490	Fax: 49-2131-349-222
Mexico City, Mexico	52555-567-7011	Fax: 52555-368-0418
Singapore	65-6285-9322	Fax: 65-6284-5843

PRINTED IN U.S.A.

KLZ 2:62EB

GPS-RevA-01/04



